

Endless possibilities across the range...

# sliding windows



Bi-folds | Stackers | Pivot Doors | Double Glazed | Sashless | Louvres | Frameless | Shopfronts



**Australian**  
Owned & Made

MCG Windows & Doors products are proudly made in Australia and designed specifically to meet all Australian conditions

**Note:** Products may be subject to local variation, regulatory requirements and confirmation of structural performance



Residential & Commercial Windows 1300 766 349

Visit [mcgwindows.com.au](http://mcgwindows.com.au)

For more information call **1300 766 349**

**Head Office**  
2-4 Jesmond Road, Croydon  
Fax 9723 9780

**Mornington Branch**  
61A / 1140 Nepean Hwy, Mornington  
Fax 5973 6841

Email [sales@mcgwindows.com.au](mailto:sales@mcgwindows.com.au)



Residential & Commercial Windows 1300 766 349







essential range

Features and Benefits

- 52mm width frame makes cleaning a breeze – most vacuum heads fit easily in track
- Clear sight lines with concealed rails
- Integrated insect, safety and security screen options
- Optional keyed vent lock allows the window to be left partially open for ventilation
- Full joint sealing for superior weather proofing performance

**Note:** Features, benefits and performance parameters are subject to local variations, climate requirements and confirmation of structural performance

Performance Parameters

Frame size	52mm
Maximum window height	1500mm (without low lites)
Maximum window width	3010mm
Maximum panel width	1500mm
Maximum panel weight	24kgs
Maximum water rating	600Pa
Maximum wind rating	4500Pa ULS
Maximum glass thickness	6.76mm (single glazed) 16mm (IGUs)
Maximum acoustic rating	Rw29
Maximum bushfire attack level	BAL 40



signature range

Features and Benefits

- Shares the clean, contemporary look of other MCG Windows & Doors Signature products
- Euro track roller system ensures smooth sliding action
- Handle has mortice lock for superior security
- Stacking configurations available for serverly situations
- Integrated insect, safety and security screen options
- Santoprene carbon seals for improved sealing and UV stability
- Wider glazing pocket for superior acoustic and thermal performance
- No visible raw edges of aluminium from section machining

Performance Parameters

Frame sizes	67mm / 100mm
Maximum window height	2000mm (without low lites)
Maximum window width	5400mm
Maximum panel width	1350mm
Maximum panel weight	100kgs
Maximum water rating	600Pa
Maximum wind rating	6000Pa ULS
Maximum glass thickness	12.76mm (single glazed) 18mm (IGUs)
Maximum acoustic rating	Rw33
Maximum bushfire attack level	BAL 40

